

Kennedy 125x3x22.2mm C24RBF FLAT STONE CUTTING DISC



Type 41 Flat Reinforced Cutting For use with all portable angle grinders. 180mm to 230mm discs can also be used on circular saws, and 300 to 350mm discs are for use with chop saws/cut-off machines, subject to bore compatibility. Not to be used for wet cutting. Grade A24/A36 - For general-purpose cutting on metals. Grade C24 - For general-purpose cutting on stone. Depressed Centre & Flat Reinforced Cutting & Grinding Discs All Kennedy Depressed Centre and Flat Reinforced Cutting Wheels now carry the oSa (The Organisation for the Safety of Abrasives) mark of approval. oSa is an association of the world's leading abrasives manufacturers. In France, it is mandatory to use only oSa-certified rough grinding wheels and cutting wheels. Similarly in Germany and Italy, it is strongly recommended that abrasive products conform to the relevant EN standards. oSa marked products are guaranteed to meet or exceed the highest worldwide safety standards, including those of the Comité Européen de Normalisation (CEN), the European standards body that issues EN standards, and of ANSI in the USA.

Specifications	Details
Weight	1
Bond Type	Resin Bonded with Fibre Reinforcement
Special Features	Good Performance Competitively Priced
Disc Diameter	125 mm
Abrasive Material	Silicon Carbide
Bore	22
Hardness	Hard
Additional Conformity	Complies to oSa Regulations Manufactured According to EN12413
Thickness	3.2 mm
Series	Stone

Specifications	Details
Grain Size	24-Coarse
Maximum RPM	12200
Optimum Angle For Use	90 Å°
SKU	KEN2306970GTSK
Type	Type 41
For Use On	Brick Concrete Roof Tiles Sand-Lime Stone Slate Stone
Product Number	1125015
Grade Designation	C24T-BF
Cutting Application	Building Construction Site Roofing
Brand	Kennedy

