

## Kennedy 100x3x16mm A24RBF FLAT CUTTING DISC



Type 41 Flat Reinforced Cutting For use with all portable angle grinders. 180mm to 230mm discs can also be used on circular saws, and 300 to 350mm discs are for use with chop saws/cut-off machines, subject to bore compatibility. Not to be used for wet cutting. Grade A24/A36 - For general-purpose cutting on metals. Grade C24 - For general-purpose cutting on stone. Depressed Centre & Flat Reinforced Cutting & Grinding Discs All Kennedy Depressed Centre and Flat Reinforced Cutting Wheels now carry the  (The Organisation for the Safety of Abrasives) mark of approval.  is an association of the world's leading abrasives manufacturers. In France, it is mandatory to use only oSa-certified rough grinding wheels and cutting wheels. Similarly in Germany and Italy, it is strongly recommended that abrasive products conform to the relevant EN standards.  marked products are guaranteed to meet or exceed the highest worldwide safety standards, including those of the Comité Européen de Normalisation (CEN), the European standards body that issues EN standards, and of ANSI in the USA.

| Specifications        | Details                                                       |
|-----------------------|---------------------------------------------------------------|
| Bore                  | 16                                                            |
| Hardness              | Hard                                                          |
| Additional Conformity | Complies to oSa Regulations Manufactured According to EN12413 |
| Weight                | 1                                                             |
| Product Number        | 1100015                                                       |
| Series                | General Purpose                                               |
| Grain Size            | 24-Coarse                                                     |
| Maximum RPM           | 15200                                                         |
| Optimum Angle For Use | 90 °                                                          |
| Thickness             | 3 mm                                                          |

| Specifications      | Details                                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Grade Designation   | A24RBF                                                                                                                              |
| Cutting Application | Cast Construction Steel alloyed & unalloyed General Purpose use on Steel Steel Cable Steel Profiles Tank Construction & Fabrication |
| Bond Type           | Resin Bonded with Fibre Reinforcement                                                                                               |
| Special Features    | Good Performance Competitively Priced                                                                                               |
| Type                | Type 41                                                                                                                             |
| For Use On          | Non Ferrous Metal                                                                                                                   |
| Disc Diameter       | 100 mm                                                                                                                              |
| Abrasive Material   | Aluminium Oxide                                                                                                                     |
| SKU                 | KEN2305080GTSK                                                                                                                      |
| Brand               | Kennedy                                                                                                                             |

