

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538



Chicago Pneumatic CP2012 Screwdrivers - Shut off 2-5 1/2NM

Productivity improved. Ideal for multiple applications. Fast cycle times for productivity. Ideal for centering screws during the fastening cycle.Range: 2 - 5 1/2 Nm 1.475 - 4.056 ft.lbs

Specifications	Details
Model Number	CP2012
Output drive	1/4"
Sound pressure	73 db(A)
Clutch type	Shut off
Min working torque	Metric: 2 Nm Imperial: 1.475 ft.lbs
Bit holder	Quick Change Hexagonal Female
Vibration uncertainty (K)	- m/s²
Screw type soft	x
Screw type hard	x
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Handle Type	Straight
Product Number	6151922012
Diameter	Metric: 34 mm Imperial: 1.33"
Free speed air consumption	Metric: 9 l/s Imperial: 19.1 cfm
Net weight	Metric: 0.9 kg Imperial: 2 lb
Max working torque	Metric: 5 1/2 Nm Imperial: 4.056 ft.lbs
Free Speed	1470 rpm
Air inlet thread size	1/4"
Length	Metric: 278 mm Imperial: 10.9"

P.O Box 25898 Sharjah United Arab Emirates

Phone : 06-5436933/06-5436733

Fax : 06-5437077

E-Mail : gentech@eim.ae Website : www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel:+966 (0) 3 834 4264

Fax: +966 3 834 4538

Specifications	Details
Brand	Chicago Pneumatic
Vibration ISO	ISO-28927-2

P.O Box 25898 Sharjah United Arab Emirates E-Mail:gentech@eim.ae Phone : 06-5436933/06-5436733 Website: www.generaltech.ae Fax : 06-5437077