

UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538

Chicago Pneumatic CP2622 Screwdrivers -Shut off 1/2-4.5NM



Productive, Accurate & Comfortable. Excellent for moderate to intensive assembly line. Productivity thanks to high speed. Easy to operate thanks to ergonomics features. Excellent accuracy for versatile applications.Range: 1/2-4.5 Nm 0.368-3.32 ft.lbs

| Specifications | Details |
|----------------------------|---------------------------------------|
| Vibration ISO | ISO-28927-2 |
| Max working torque | Metric: 4.5 Nm Imperial: 3.32 ft.lbs |
| Screw type soft | X |
| Screw type hard | x |
| Bit holder | Quick Change Hexagonal Female |
| Vibration uncertainty (K) | - m/sÂ ² |
| Min working torque | Metric: 1/2 Nm Imperial: 0.368 ft.lbs |
| Product Number | 6151922622 |
| Brand | Chicago Pneumatic |
| Length | Metric: 232 mm Imperial: 9.1" |
| Model Number | CP2622 |
| Output drive | 1/4" |
| Sound pressure | 75 db(A) |
| Clutch type | Shut off |
| Diameter | Metric: 42 mm Imperial: 1.65" |
| Sound Power | 86 db(A) |
| Air inlet thread size | 1/4" |
| Free speed air consumption | Metric: 13.7 l/s Imperial: 29 cfm |



UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538

| Specifications | Details |
|----------------|----------------------------------|
| Net weight | Metric: 0.8 kg Imperial: 1.76 lb |
| Min. Hose Size | Metric: 10 mm Imperial: 3/8" |
| Free Speed | 1700 rpm |
| Handle Type | Straight |

×