

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538



Chicago Pneumatic CP8548K Pack US Cordless electric tools - Cordless drills 82NM

Strong & versatile. 3 modes (screwing, drilling and hammer drilling). Independent LED lighting for dimly lit work surfaces. Electronic trigger with varaible speed. Ergonomic handle fits your hand perfectly.Range: 82 Nm 60 ft.lbs

Brand Chicago Pneumatic Model Number CP8548K Pack USÂ Square Drive 13 mm Length Metric: 240 mm Imperial: 9.6" Net weight Metric: 2.4 kg Imperial: 5.3 lb Sound pressure 88 db(A) Sound Power 99 db(A) Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb Chuck size Metric: 1.5 - 13 mm Imperial: 1/16" - 1/2"	Specifications	Details
Model Number CP8548K Pack USÂ Square Drive 13 mm Length Metric: 240 mm Imperial: 9.6" Net weight Metric: 2.4 kg Imperial: 5.3 lb Sound pressure 88 db(A) Sound Power 99 db(A) Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Product Number	8941085481
Square Drive 13 mm Length Metric: 240 mm Imperial: 9.6" Net weight Metric: 2.4 kg Imperial: 5.3 lb Sound pressure 88 db(A) Sound Power 99 db(A) Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Brand	Chicago Pneumatic
Length Metric: 240 mm Imperial: 9.6" Net weight Metric: 2.4 kg Imperial: 5.3 lb Sound pressure 88 db(A) Sound Power 99 db(A) Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Model Number	CP8548K Pack USÂ
Net weight Sound pressure 88 db(A) Sound Power 99 db(A) Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Square Drive	13 mm
Sound pressure 88 db(A) Sound Power 99 db(A) Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Length	Metric: 240 mm Imperial: 9.6"
Sound Power 99 db(A) Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Net weight	Metric: 2.4 kg Imperial: 5.3 lb
Vibration ISO ISO- Vibration uncertainty (K) 1 1/2 m/s² Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Sound pressure	88 db(A)
Vibration uncertainty (K)1 1/2 m/s²Battery voltage20 VBattery type4Ah 20V Lithium-ionWeight without batteryMetric: 1.68 kg Imperial: 3.7 lb	Sound Power	99 db(A)
Battery voltage 20 V Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Vibration ISO	ISO-
Battery type 4Ah 20V Lithium-ion Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Vibration uncertainty (K)	1 1/2 m/sÂ ²
Weight without battery Metric: 1.68 kg Imperial: 3.7 lb	Battery voltage	20 V
	Battery type	4Ah 20V Lithium-ion
Chuck size Metric: 1.5 - 13 mm Imperial: 1/16" - 1/2"	Weight without battery	Metric: 1.68 kg Imperial: 3.7 lb
	Chuck size	Metric: 1.5 - 13 mm Imperial: 1/16" - 1/2"
Drilling capacity in steel Metric: 13 mm Imperial: 1/2"	Drilling capacity in steel	Metric: 13 mm Imperial: 1/2"
Drilling capacity in wood Metric: 55 mm Imperial: 2.16"	Drilling capacity in wood	Metric: 55 mm Imperial: 2.16"

P.O Box 25898 Sharjah United Arab Emirates Phone : 06-5436933/06-5436733

Fax : 06-5437077

E-Mail : gentech@eim.ae Website : www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel: +966 (0) 3 834 4264

Fax: +966 3 834 4538

Specifications	Details
Drilling capacity in brick & tile	Metric: 16 mm Imperial: 0.63"
Wood screws (without pre-drilling)	Metric: 8 mm Imperial: 5/16"
Max torque	Metric: 82 Nm Imperial: 60 ft.lbs
Stall torque	Metric: 82 Nm Imperial: 60 ft.lbs
Free Speed	0 - 1600 rpm
Free speed 1st gear	0 - 450 rpm
Free speed 2nd gear	0 - 1600 rpm
Percussion under load 1st gear	7200 /min
Percussion under load 2nd gear	25600 /mi

P.O Box 25898 Sharjah United Arab Emirates E-Mail:gentech@eim.ae Phone : 06-5436933/06-5436733 Website: www.generaltech.ae Fax : 06-5437077