

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538



## Norton Saint Gobain.180x7,0x22,23mm METAL - I NOX MEDIUM

Industrial Line - Type 27 DC Medium Advanced grain and bond system for longer life and quicker cutting. Suitable for steel and stainless steel applications. Free from iron, sulphur and chloride.

Type Type 27  For Use On Stainless Steel Steel  Grade Designation A24R-BF  Cutting Application Sheet Steel Steel Profiles Tank Construction & Fabrication Welding Seams  Abrasive Material Aluminium Oxide  Hardness Hard  Thickness 7.0 mm  Series Industrial line  Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS  Special Features Free From Iron, Sulpher and Chlorine Superior Bond System	Specifications	Details	
Grade Designation A24R-BF  Cutting Application Sheet Steel Steel Profiles Tank Construction & Fabrication Welding Seams  Abrasive Material Aluminium Oxide  Hardness Hard  Thickness 7.0 mm  Series Industrial line  Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Type	Type 27	
Cutting Application Sheet Steel Steel Profiles Tank Construction & Fabrication Welding Seams  Abrasive Material Aluminium Oxide  Hardness Hard  Thickness 7.0 mm  Series Industrial line  Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	For Use On	Stainless Steel Steel	
Abrasive Material Aluminium Oxide  Hardness Hard  Thickness 7.0 mm  Series Industrial line  Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Grade Designation	A24R-BF	
Hardness Hard Thickness 7.0 mm  Series Industrial line Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Cutting Application	Sheet Steel Steel Profiles Tank Construction & Fabrication Welding Seams	
Thickness 7.0 mm  Series Industrial line  Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Abrasive Material	Aluminium Oxide	
Series Industrial line  Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Hardness	Hard	
Additional Conformity Complies to oSa Regulations Manufactured According to EN12413  Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Thickness	7.0 mm	
Bond Type Resin Bonded with Fibre Reinforcment  Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Series	Industrial line	
Grain Size 24-Coarse  Maximum RPM 8500  SKU NOR2303258GTSS	Additional Conformity	Complies to oSa Regulations Manufactured According to EN12413	
Maximum RPM 8500 SKU NOR2303258GTSS	Bond Type	Resin Bonded with Fibre Reinforcment	
SKU NOR2303258GTSS	Grain Size	24-Coarse	
	Maximum RPM	8500	
Special Features Free From Iron, Sulpher and Chlorine Superior Bond System	SKU	NOR2303258GTSS	
	Special Features	Free From Iron, Sulpher and Chlorine Superior Bond System	
Benefits Fast Cutting High Material Removal rate Long Product Life	Benefits	Fast Cutting High Material Removal rate Long Product Life	
Brand Norton	Brand	Norton	

P.O Box 25898 Sharjah United Arab Emirates

Phone : 06-5436933/06-5436733

Fax : 06-5437077

E-Mail : gentech@eim.ae Website : www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel:+966 (0) 3 834 4264

Fax: +966 3 834 4538

pecifications	Details
ht.	1

P.O Box 25898 Sharjah United Arab Emirates

Phone : 06-5436933/06-5436733 Fax : 06-5437077

E-Mail:gentech@eim.ae Website: www.generaltech.ae