

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

E-Mail:gentech@eim.ae

Website: www.generaltech.ae

## Isotech Jupiter 4852 |35°C to 660°C Calibrator

The Jupiter Dry Block range offers industry-leading performance in an easy to use portable package - ideal for the calibration of thermocouples and platinum resistance thermometers. It has been designed for fast heating and cooling for convenient field use. For flexibility surface sensor and infrared thermometer accessories can be added. The standard insert can hold up to six thermometers. For larger blocks see the Gemini range. These award winning calibrators are easy to use and are available in three versions â∏ the Basic, the Site and the ADVANCED. The Basic has a digital display of set and nominal temperature, the Site additionally includes an inbuilt independent temperature indicator for a reference probe. The ADVANCED controller has inputs for reference and test thermometers with a further range of sophisticated features including automatic temperature cycling, secure data logging and full colour high resolution display. Isotech is a world leader in temperature calibration, providing many nations with their Primary Standards and operates a full scale UKAS accredited calibration laboratory. We can offer a range of calibration options to meet your requirements. Benefit from our experience and understanding in calibration at all levels, our evaluation reports, our tutorials and uncertainty calculations. These models meet the calibration capacity requirements of EURAMET/cg-13/v.01, â∏EA Guidelines on the Calibration of Temperature Block Calibrators, formerly EA10/13. All models include I-Cal Easy LOG software and the ADVANCED models additionally include software to manage logged data and configure the unit, more details.

Specifications	Details	
Brand	Isotech	
Power	115Vac or 230Vac 50/60Hz 1000 Watts	
Temp Range	35°C to 660°C	
Display Resolution	$0.01 {\rm \^{A}}^{\circ}{\rm C}$ from 30.00 to 99.99 ${\rm \^{A}}^{\circ}{\rm C}$ then $0.1 {\rm \^{A}}^{\circ}{\rm C}$ : $0.01 {\rm \^{A}}^{\circ}{\rm C}$ Over PC Interface	
Weight	8.5kg	
Stability	±0.02°C @ 100°C ±0.03°C @ 650°C	
Standard Insert	6 pockets, 2 x 4.5mm, 2 x 6.4mm, 1 x 8.0mm, 1 x 9.5mm diameter, all 140mm deep	
Calibration Volume	35mm diameter by 148mm deep	
Cools from 650°C to 150°C	in 60 minutes	
Heats from 30°C to 650°C	in 20 minutes	



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

Specifications	Details
Blackbody Source	±0.3°C
Surface Sensor Calibrator	±0.5°C
Indiactor Units	°C, °F, K

P.O Box 25898 Sharjah United Arab Emirates E-Mail:gentech@eim.ae Phone : 06-5436933/06-5436733 Website: www.generaltech.ae Fax : 06-5437077