

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

Isotech Gemini 4857-550 |35°C to 550°C Calibrator



The Gemini range of Dry Blocks have high capacity allowing a large number of probes to be calibrated together. They are also suitable to accept large diameter probes with the block volume of a nominal 64 x 160mm. Whilst the large block takes longer to heat and cool than the Jupiter it can calibrate thermocouples, resistance thermometers, thermostats and sensors that are too large for the smaller blocks. These award winning calibrators are easy to use and are available in three versions â∏ the Basic, the Site and the ADVANCED. The Basic has a digital display of set and nominal temperature, the Site additionally includes an inbuilt independent temperature indicator for a reference probe. The ADVANCED controller has inputs for reference and test thermometers with a further range of sophisticated features including automatic temperature cycling, secure data logging and full colour high resolution display. All models include I-Cal Easy LOG software and the ADVANCED models additionally include software to manage logged data and configure the unit. Available with a fixed block with four 8mm and four 19.5mm pockets or the LRI version which has a removable block. With the LRI model, blocks can be drilled to custom configurations. Isotech is a world leader in temperature calibration, providing many nations with their Primary Standards and operates a full scale UKAS accredited calibration laboratory. We can offer a range of calibration options to meet your requirements. These models meet the calibration capacity requirements of EURAMET/cg-13/v.01, â∏EA Guidelines on the Calibration of Temperature Block Calibrators, formerly EA10/13.

Specifications	Details
Indicator Units	°C, °F, K
Heats from 30°C to 550°C	35 mins (LRI: 60 mins)
Cools from 550°C to 275°C	in 35 mins (LRI: 132 mins)
Cools from 550°C to 60°C	in 345 mins (LRI: 420 mins)
Calibration Volume	65mm diameter, 160mm deep
Stability	±0.02°C @ 50°C ±0.03°C @ 250°C ±0.04°C @ 550°C
Weight	8.5kg
Display Resolution	$0.01 {\rm \^{A}^{\circ}C}$ from 30.00 to 99.99 ${\rm \^{A}^{\circ}C}$ then $0.1 {\rm \^{A}^{\circ}C}$: $0.01 {\rm \^{A}^{\circ}C}$ Over PC Interface
Temp Range	35°C to 550°C
Brand	Isotech

P.O Box 25898 Sharjah Phone : 06-5436933/06-5436733 E-Mail : gentech@eim.ae United Arab Emirates Fax : 06-5437077 Website : www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel:+966 (0) 3 834 4264 Fax: +966 3 834 4538

Specifications	Details
Voltage	115Vac or 230Vac 50/60Hz
Power	600 Watts (LRI: 1000 Watts)

P.O Box 25898 Sharjah United Arab Emirates E-Mail:gentech@eim.ae Phone : 06-5436933/06-5436733 Website: www.generaltech.ae Fax : 06-5437077