

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

York No.3 12x38mm AL/OX TAPER CARTRIDGE ROLL P120



Taper Type - Tapered for angles, corners and irregular or concave surfaces. Spirally wound aluminium oxide cloth rolls that wear in use constantly exposing new abrasive. Used for weld flash removal, deburring, blending and polishing applications. Available in two types. A steel mandrel must be used top secure the abrasive to the tool. Maximum Running Speeds: Up to 12mm dia. 22,000rpm. Up to 19mm dia. 18,000rpm. Up to 25mm dia. 10,000rpm.

Specifications	Details
Weight	1
Overall Length	38 mm
Diameter	12 mm
Туре	CRT3
SKU	YRK2057360GTSK
Grit	P120
Maximum Operating Speed	22000 rpm
Cartridge Shape	Taper
Brand	York

P.O Box 25898 Sharjah Phone :06-5436933/06-5436733 E-Mail :gentech@eim.ae United Arab Emirates Fax :06-5437077 Website :www.generaltech.ae