


**IIS204**

IIB3015BBPKG/M/US-104-DPS

**Inductive sensors**



Made in Germany



**Product characteristics**

Inductive sensor
Metal thread M30 x 1.5
Connector
Increased sensing range
Gold-plated contacts
Sensing range 15 mm; [f] flush mountable

**Electrical data**

Electrical design	DC PNP
Operating voltage [V]	10...36 DC
Current consumption [mA]	< 10 (24 V)
Protection class	II
Reverse polarity protection	yes

**Outputs**

Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	100
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	100

**Range**

Sensing range [mm]	15
Real sensing range (Sr) [mm]	15 ± 10 %
Operating distance [mm]	0...12.1

**Accuracy / deviations**

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3
Hysteresis [% of Sr]	3...15
Switch-point drift [% of Sr]	-10...10

**Environment**

Ambient temperature [°C]	-25...70
Protection	IP 67

**Tests / approvals**

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated: 10 V/m (80...1000 MHz)
	EN 61000-4-4 Burst: 2 kV
	EN 61000-4-6 HF conducted: 10 V (0.15...80 MHz)
	EN 55011: class B

## IIS204

IIB3015BBPKG/M/US-104-DPS

Inductive sensors

MTTF	[Years]	1992
------	---------	------

### Mechanical data

Mounting		flush mountable
Housing materials		Brass white bronze coated; active face: PBT
Weight	[kg]	0.119


### Displays / operating elements

Output status indication	LED	yellow (4 x 90°)
--------------------------	-----	------------------

### Electrical connection

Connection		M12 connector; Gold-plated contacts
------------	--	-------------------------------------

### Wiring



### Accessories

Accessories (included)		2 lock nuts
------------------------	--	-------------

### Remarks

Pack quantity	[piece]	1
---------------	---------	---