



NORTORQUE®



The NorTorque® utilises Norbar's proven mechanism and internal components and incorporates them into a purposeful and attractive torque wrench that will delight a wide range of users from professional mechanics to hobby enthusiasts

- Accurate to $\pm 3\%$ of reading which meets the requirements of ISO 6789-1:2017
- Light and fast adjustment saves operator time and effort
- Micrometer scale applying to the primary torque units (N·m on a dual scale wrench) for simple and error-free setting
- 'Push-through' ratchets allow torque control in both the clockwise and counter-clockwise directions
- Tough ratchets with narrow engagement angles allow for easy positioning of the tool in confined spaces (5° for models up to 200 N·m and 6° for models 300 N·m and above)
- Push/pull lock is fast and intuitive to use and prevents accidental adjustment of the set torque
- Convenient hanger feature for tool storage also aids wrench unlocking and adjustment
- Tethered versions are available for working at height (see page 28)



2	RATCHET ADJUSTABLE - DUAL SCALE	
130101*	Model 60, $\frac{3}{8}$ ", 12 - 60 N·m, 10 - 45 lbf·ft	
130103	Model 100, $\frac{1}{2}$ ", 20 - 100 N·m, 20 - 80 lbf·ft	
130104	Model 200, $\frac{1}{2}$ ", 40 - 200 N·m, 30 - 150 lbf·ft	
130105	Model 300, $\frac{1}{2}$ ", 60 - 300 N·m, 45 - 220 lbf·ft	
130106	Model 340, $\frac{1}{2}$ ", 60 - 340 N·m, 45 - 250 lbf·ft	


2	RATCHET ADJUSTABLE - N·m ONLY	
130111*	Model 60, $\frac{3}{8}$ ", 12 - 60 N·m	
130113	Model 100, $\frac{1}{2}$ ", 20 - 100 N·m	
130114	Model 200, $\frac{1}{2}$ ", 40 - 200 N·m	
130115	Model 300, $\frac{1}{2}$ ", 60 - 300 N·m	
130116	Model 340, $\frac{1}{2}$ ", 60 - 340 N·m	

* Supplied with $\frac{1}{2}$ " sq. dr. adaptor
 · Supplied with $\frac{3}{8}$ " sq. dr. adaptor



2	FEMALE TORQUE HANDLE ADJUSTABLE - DUAL SCALE	
130121	Model 60, 9 x 12 mm, 12 - 60 N·m, 10 - 45 lbf·ft	
130123	Model 100, 9 x 12 mm, 20 - 100 N·m, 20 - 80 lbf·ft	
130125	Model 200, 9 x 12 mm, 40 - 200 N·m, 30 - 150 lbf·ft	
130126	Model 200, 14 x 18 mm, 40 - 200 N·m, 30 - 150 lbf·ft	
130127	Model 300, 14 x 18 mm, 60 - 300 N·m, 45 - 220 lbf·ft	
130128	Model 340, 14 x 18 mm, 60 - 340 N·m, 45 - 250 lbf·ft	

2	FEMALE TORQUE HANDLE ADJUSTABLE - N·m ONLY	
130131	Model 60, 9 x 12 mm, 12 - 60 N·m	
130133	Model 100, 9 x 12 mm, 20 - 100 N·m	
130135	Model 200, 9 x 12 mm, 40 - 200 N·m	
130136	Model 200, 14 x 18 mm, 40 - 200 N·m	
130137	Model 300, 14 x 18 mm, 60 - 300 N·m	
130138	Model 340, 14 x 18 mm, 60 - 340 N·m	



2	TORQUE HANDLE ADJUSTABLE 16 mm SPIGOT - DUAL SCALE	
130141	Model 60, 16 mm spigot, 12 - 60 N·m, 10 - 45 lbf·ft	
130142	Model 100, 16 mm spigot, 20 - 100 N·m, 20 - 80 lbf·ft	
130143	Model 200, 16 mm spigot, 40 - 200 N·m, 30 - 150 lbf·ft	
130144	Model 300, 16 mm spigot, 60 - 300 N·m, 45 - 220 lbf·ft	

2	TORQUE HANDLE ADJUSTABLE 16 mm SPIGOT - N·m ONLY	
130161	Model 60, 16 mm spigot, 12 - 60 N·m	
130162	Model 100, 16 mm spigot, 20 - 100 N·m	
130163	Model 200, 16 mm spigot, 40 - 200 N·m	
130164	Model 300, 16 mm spigot, 60 - 300 N·m	