


**PK6523**

PK-025-SFG14-HCPKG/US/ W

Pressure sensors



1: sealing FPM / DIN 3869-14



**Product characteristics**

Electronic pressure monitor

Connector

Process connection: G ¼ A / M5 I

2 switching outputs  
normally open / closed complementary

Measuring range: 0...25 bar / 0...363 psi

**Application**

Application	Type of pressure: relative pressure Liquids and gases	
Pressure rating	60 bar	870 psi
Bursting pressure min.	500 bar	7253 psi
Medium temperature [°C]	-25...80	

**Electrical data**

Electrical design	DC PNP	
Operating voltage [V]	9.6...32 DC	
Current consumption [mA]	< 25	
Insulation resistance [MΩ]	> 100 (500 V DC)	
Protection class	III	
Reverse polarity protection	yes	

**Outputs**

Output	2 switching outputs normally open / closed complementary	
Output function	complementary	
Current rating [mA]	500	
Voltage drop [V]	< 2	
Short-circuit protection	pulsed	
Overload protection	yes	
Switching frequency [Hz]	100	


**Measuring / setting range**

Measuring range	0...25 bar	0...363 psi
Setting range		
Set point, SP	1.25...25 bar	18...363 psi
Reset point, rP	0.75...24.5 bar	11...355 psi

**PK6523**

PK-025-SFG14-HCPKG/US/ W

Pressure sensors

Accuracy / deviations	
Deviations (% of value of measuring range)	
Switch point accuracy	< ± 2.5 *
Characteristics deviation	< ± 1.5 (BFSL) / < ± 2.5 (LS) **)
Repeatability	< ± 0.5
Temperature drift ( / 10 K)	< ± 0.5
in the temperature range [°C]	0...80
Software / programming	
Adjustment of the switch point	setting rings
Environment	
Ambient temperature [°C]	-25...80
Storage temperature [°C]	-40...100
Protection	IP 67
Tests / approvals	
EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-5 Surge: 1 kV signal for DC units EN 61000-4-6 HF conducted: 10 V
Shock resistance	DIN IEC 68-2-27: 50 g (11 ms)
Vibration resistance	DIN IEC 68-2-6: 20 g (10...2000 Hz)
MTTF [Years]	540
Mechanical data	
Process connection	G ¼ A / M5 I
Materials (wetted parts)	stainless steel 316L / 1.4404; FPM (Viton)
Housing materials	PBT (Pocan); PC (Makrolon); FPM (Viton); stainless steel 316L / 1.4404
Switching cycles min.	50 million
Tightening torque [Nm]	25
Weight [kg]	0.093
Displays / operating elements	
Display	Operation LED green Switching status LED yellow
Electrical connection	
Connection	M12 connector
<b>Wiring</b>	
Remarks	
Remarks	*) Setting accuracy **) BFSL = Best Fit Straight Line / LS = Limit Value Setting
Pack quantity [piece]	1