

TECHNICAL DATA



Features

- Measures AC/DC voltage and current, frequency, resistance, capacitance and temperature
- Diode check and continuity functions
- Relative and data hold functions
- Double molded plastic housing
- Cat. III 600V safety rating
- Includes Thermocouple Adapter, thermocouple wire probe (Type K), test leads, battery and carrying case

Specifications

AC/DC Voltage

Range: AC: 400mV, 4, 40, 400, 600V
DC: 400mV, 4, 40, 400, 600V

Accuracy: AC: 400mV \pm (15% rdg. + 15 dgt.)
4V \pm (1.2% rdg. + 3 dgt.)
40, 400V \pm (1.5% rdg. + 3 dgt.)
600V \pm (2.0% rdg. + 4 dgt.)
DC: 400mV \pm (0.05% rdg. + 2 dgt.)
4, 40, 400V \pm (1.2% rdg. + 2 dgt.)
600V \pm (1.5% rdg. + 2 dgt.)

Resolution: AC: 0.1mV, 1, 10, 100V
DC: 0.1mV, 1, 10, 100V

AC/DC Current

Range: 400, 4000 μ A, 40, 400mA, 10A

Accuracy: AC: 400 μ A \pm (1.5% rdg. + 5 dgt.)
4000 μ A/40, 400mA \pm (1.8% rdg. + 5 dgt.)
10A \pm (3.0% rdg. + 7 dgt.)
DC: 400 μ A \pm (1.0% rdg. + 3 dgt.)
4000 μ A/40, 400mA \pm (1.5% rdg. + 3 dgt.)
10A \pm (2.5% rdg. + 5 dgt.)

Resolution: 0.1, 1 μ A, 10, 100mA, 1A

Resistance

Range: 400 Ω , 4, 40, 400k Ω , 4, 40M Ω

Accuracy: 400 Ω : \pm (1.2% rdg. + 4 dgt.)
4k Ω : \pm (1.0% rdg. + 2 dgt.)
40, 400k Ω , 4M Ω : \pm (1.2% rdg. + 2 dgt.)
40M Ω : \pm (2.0% rdg. + 3 dgt.)

Resolution: 0.01 Ω , 1, 10, 100k Ω , 1, 10M Ω

Capacitance

Range: 4, 40, 400nF, 4, 40, 200 μ F

Accuracy: 4nF: \pm (5.0% rdg. + 50 dgt.)
40nF: \pm (5.0% rdg. + 7 dgt.)
400nF/4, 40 μ F: \pm (3% rdg. + 5 dgt.)
200 μ F: \pm (5% rdg. + 5 dgt.)

Resolution: 1, 10pF, 0.1, 1, 10nF, 0.1 μ F

Frequency

Range: 9.999, 99.99, 999.9Hz, 9.999, 99.99, 999.9KHz, 9.999MHz

Accuracy: 9.999, 99.99Hz: \pm (1.5% rdg. + 5 dgt.)
999.9Hz, 9.999, 99.99, 999.9KHz: \pm (1.2% rdg. + 3 dgt.)
9.999MHz: \pm (1.5% rdg. + 4 dgt.)

Resolution: 0.001, 0.01, 0.1, 1, 10, 100Hz, 1kHz

Temperature

Range: -4 to 1400 $^{\circ}$ F (-20 to 760 $^{\circ}$ C)

Accuracy: \pm (3.0% rdg. + 9 $^{\circ}$ F)
 \pm (3.0% rdg. + 5 $^{\circ}$ C)

Resolution: 1 $^{\circ}$ F, 1 $^{\circ}$ C

Continued...



TECHNICAL DATA

General Specifications

Range Selection:	Autoranging/Manual
Display:	4,000 count LCD display
Display Hold:	Yes
Peak Hold:	Yes
Relative Mode:	Yes
Diode Test:	Yes
Continuity Check:	Audible signal if resistance $\leq 150\Omega$
Duty Cycle:	Yes (0.1 - 99.9%)
Kick Stand:	Yes
Auto Power Off:	Yes (after 15 minutes)
Power Supply:	9V Battery
Low Battery Indicator:	Yes
Fuse Protection:	Yes
Replaceable Test Leads:	Yes
Oversvoltage Category:	CAT. III 600V
Product Certifications:	CE
Operating Temperature:	32 to 122°F (0 to 50°C)
Storage Temperature:	-4 to 140°F (-20 to 60°C)
Dimensions:	5.9 x 2.8 x 1.9" (150 x 70 x 48mm)
Weight:	9oz (255g)

Model	Description
R5008	Multimeter with Temperature
FC-300	Fused Test Lead Set
P-15	Weatherproof Plug
CP-09	AC Current Adapter
AD-1	Thermocouple Adapter
TP-01	Type K Thermocouple Wire Probe
R1000	Safety Test Lead Set, Double Insulated
R2920	Surface Thermocouple Probe
R2930	Right Angle Thermocouple Surface Probe
R2950	Immersion Thermocouple Probe
CA-52A	Soft Carrying Case
R5008-NIST	Multimeter with Temperature & NIST