# Data Logging Indoor Air Quality Meter Model **R9905**



# TECHNICAL DATA

### Features

- Triple LCD display simultaneously monitors carbon dioxide (CO<sub>2</sub>), temperature and relative humidity
- Calculates time-weighted average (TWA) and short-term exposure limit (STEL)
- Low-drift NDIR CO<sub>2</sub> sensor for stable and accurate readings
- Temperature and relative humidity measurements help determine thermal comfort
- Easy-to-read backlit LCD display
- User adjustable audible alarm
- Data hold, Max/Min and Average functions
- Record up to 32,000 datapoints and keep track with internal time and date stamp
- User selectable sampling rate from 1 to 60 mins
- Low battery indicator and auto shut-off
- Includes USB cable, hard carrying case and batteries

### **Specifications**

#### Temperature

Measuring Range: Accuracy: Resolution: -4 to 140°F (-20 to 60°C) ±1.5°F (±0.8°C) 0.1°F/°C

#### Humidity

Resolution:

Measuring Range: Accuracy: 0 to 100% RH 10 to 90% RH: ±3% <10% & >90% RH: ±5% 0.1% RH

#### CO<sub>2</sub> (Carbon Dioxide)

Sensor Type: Measuring Range: Accuracy:

Resolution: Warm-up Time: Sampling Rate: Nondispersive Infrared (NDIR) O to 30,000ppm O to 5000ppm: ±(75ppm + 3% rdg.) 5001 to 30,000ppm: ±(150 ppm +5% rdg.) 1ppm 20 seconds 2 seconds



Continued...

# **REED** Instruments



Data Logging Indoor Air Quality Meter Model R9905



# TECHNICAL DATA

## General Specifications

LCD

Yes

Yes

Display: Backlit Display: Data Hold: Min, Max, Avg Functions: Short Term رCO Exposure Limit (STEL): Time Weighted رCO Average (TWA): Datalogging Capabilities: Real-Time Clock and Date Stamp: Selectable Sampling Rate: Internal Memory: Alarm: Auto Shut-off: Kick Stand: Low Battery Indicator: Power Supply: Battery Life:

PC Connectivity: Software OS Compatibility: Product Certifications: Operating Temperature: Storage Temperature: Operating Humidity Range: Storage Humidity Range: Maximum Operating Altitude: Dimensions:

Weight:

Yes Yes (15 minutes) Yes (8 hours) Yes Yes Yes (between 1s and 60m59s) Yes (32,000 datapoints) Yes (Low and High) Yes (adjustable) Yes Yes 9V battery Approx. 10 hours (continuous use) USB Windows 7/8/10 CE 32 to 122°F (O to 50°C) -4 to 140°F (-20 to 60°C) O to 90% 10 to 75%

6561' (2000m) 11.2 x 2.6 x 1.5" (284 x 65 x 39mm) 10.7oz (304g)

Model	Description
R9905	Data Logging Indoor Air Quality Meter
R9905-PROBE	Replacement Temperature & Humidity Probe
R9905-NIST	Data Logging Indoor Air Quality Meter with NIST